

# MATERIAL SAFETY DATA SHEET

PRODUCT NAME: EPOXY GROUT "PART A"  
 PRODUCT CODE: 3042

HMIS CODES: H F R P  
 2 1 0 F

## ===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: Custom Building Products, Inc.  
 ADDRESS: 6511 SALT LAKE AVE., BELL, CA. 90201  
 EMERGENCY PHONE: (323) 582-0846 INFORMATION PHONE: (323) 582-0846  
 DATE REVISED : 6-20-03 NAME OF PREPARER : STEVE TAYLOR  
 REASON REVISED : Updated Carcinogenicity Information

## ===== SECTION II - INGREDIENTS/SARA III INFORMATION =====

COMPONENTS	CAS NUMBER	OCCUPATIONAL EXPOSURE LIMITS		VAPOR PRESSURE	Wt. %
		OSHA PEL	ACGIH TLV	mm Hg @ TEMP	----
BISPHENOL ALKYL (C12-C14)	25068-38-6	N/E	N/E	N/E	
GLYCIDYL ETHER	68609-97-2	N/E	N/E	N/E	

\* No toxic chemical(s) are subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

N/E= Not Established.

## ===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: >400F SPECIFIC GRAVITY (H2O=1): 1.12 @ 77F  
 VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: NO DATA  
 SOLUBILITY IN WATER: SLIGHT  
 APPEARANCE AND ODOR: WHITE PASTE, FAINT

## ===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: >212F METHOD USED: TCC  
 FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES  
 USE SELF CONTAINED BREATHING APPARATUS.

UNUSUAL FIRE AND EXPLOSION HAZARDS  
 DECOMPOSITION AND COMBUSTION PRODUCTS MAY BE TOXIC.

## ===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE

CONDITIONS TO AVOID  
NONE

INCOMPATIBILITY (MATERIALS TO AVOID)  
MINERAL ACIDS, ORGANIC ACIDS, ALKALIS, AND OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS  
(FROM BURNING, HEATING, OR REACTION WITH OTHER MATERIALS)

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

## ===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
INHALATION OF VAPORS MAY CAUSE IRRITATION IN THE RESPIRATORY TRACT. COUGHING  
AND CHEST PAIN MAY RESULT.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
REPEATED AND/OR PROLONGED CONTACT WITH THE SKIN MAY CAUSE ALLERGIC REACTION  
REPEATED AND/OR PROLONGED EXPOSURE TO LOW CONCENTRATIONS OF VAPOR MAY CAUSE:  
EYE IRRITATION, HEADACHE, SORE THROAT.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
MINOR IRRITATION; MAY BE A SKIN SENSITIZER.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
LOW ACUTE ORAL TOXICITY; LD50 GREATER THAN 2000.

HEALTH HAZARDS (ACUTE AND CHRONIC)  
ACUTE: NONE CHRONIC: NONE

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO NONE

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE  
ASTHMA, SKIN DISORDERS AND ALLERGIES.

EMERGENCY AND FIRST AID PROCEDURES  
EYE CONTACT: FLUSH EYE WITH PLENTY OF WATER FOR FIFTEEN MINUTES.  
SKIN CONTACT: FLUSH INFECTED AREA FOR AT LEAST FIFTEEN MINUTES  
INHALED: MOVE PATIENT TO FRESH AIR. CALL A PHYSICIAN.  
SWALLOWED: CALL A PHYSICIAN IMMEDIATELY. INDUCE VOMITING. NEVER GIVE  
ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

## ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

SOAK UP IN ABSORBENT MATERIAL OR SCRAPE UP. RESIDUAL CAN BE REMOVED WITH NON-FLAMMABLE SOLVENT, SUCH AS TRICHLOROETHANE. FLUSH AREA WITH WATER SPRAY. AVOID INHALATION OF VAPORS. USE RESPIRATORY PROTECTION.

WASTE DISPOSAL METHOD

DISPOSE OF WASTE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

KEEP AWAY FROM HEAT OR OPEN FLAME. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING VAPORS.

OTHER PRECAUTIONS

NONE

## ===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

NONE REQUIRED UNDER NORMAL CONDITIONS.

VENTILATION

GOOD ROOM VENTILATION USUALLY ADEQUATE FOR MOST OPERATIONS.

PROTECTIVE GLOVES

CHEMICAL RESISTANT PLASTIC OR RUBBER.

EYE PROTECTION

SAFETY GLASSES. IN EMERGENCY SITUATIONS USE EYE GOGGLES WITH A FULL FACE SHIELD.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

LONG SLEAVED, CLEAN BODY COVERING CLOTHING.

WORK/HYGIENIC PRACTICES

PRACTICE CAUTION AND PERSONAL CLEANLINESS TO AVOID SKIN AND EYE CONTACT. AVOID BREATHING VAPORS OF HEATED PRODUCT.

## ===== SECTION IX - DISCLAIMER =====

DISCLAIMER

THE INFORMATION PRESENTED HERE IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED, THAT THE INFORMATION IS CURRENT APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.